

Dependent Resurvey, Portion of the 1st Guide Meridian East,
T. 26 N., R. 9 E., Sixth Principal Meridian, Nebraska

CHAINS	<p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° W., 55.8 lks. dist., with brass cap mkd. RM T26N R8E S1 36.8 FT. TO COR. 1997 and an arrow pointing to the cor.</p> <p>Deposit the iron pipe inside the iron post.</p> <p>Cor. is located 20 lks. S. of center of BIA Road No. 1.</p> <hr/> <p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 26 N., R. 9 E., Sixth Principal Meridian, Nebraska</p> <hr/> <p>(Restoring the survey executed by Theodore H. Barrett in 1867 and subsequent resurvey executed by John W. Beaman in 1875)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8, monumented with a granite stone, 24x18x12 ins., firmly set 12 ins. in the ground, plainly mkd. 1/4 on N. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, atop a white "DEEP-1" magnetic marker, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R9E</p> <p>S 5</p> <p>1/4 —</p> <p>S 8</p> <p>1997</p> </div> <p>Bury the original cor. stone and set a steel fence post alongside the iron post.</p> <p>Cor. is located 9 lks. N. and 29 lks. W. of cor. of fences extending N. and W.</p> <p>S. 89° 28' W., bet. secs. 5 and 8.</p> <p>Over rolling terrain.</p> <p>19.98 Point for the W. 1/16 sec. cor. of secs. 5 and 8, at proportionate distance, falls in fence extending E. and W.; there is no remaining evidence of the original monument. Point not monumented.</p>
--------	--